



Point



APPLICATION <i>APLICACIÓN</i>	Spotlight, recessed <i>Proyector a carril, empotrado</i>
POWER <i>POTENCIA</i>	15W to 25W <i>15W a 25W</i>
OPTICS <i>ÓPTICAS</i>	15° to 45° <i>15° a 45°</i>
LUMEN OUTPUT <i>FLUJO LUMINOSO</i>	850 lm to 2100 lm <i>850 lm a 2100 lm</i>
EFFICIENCY <i>EFICIENCIA</i>	88 lm/W
COLOUR TEMP. <i>T° COLOR</i>	2700K, 3000K, 4000K
CRI <i>CRI</i>	> 80 > 90 R9 >50

LIFETIME <i>VIDA</i>	190 > 30000 h to 25°C / L70 > 100000 h to 25°C <i>190 > 30000 h a 25°C / L70 > 100000 h a 25°C</i>
ORIENTATION <i>ORIENTACIÓN</i>	Horizontal 360° - Vertical 90°
CONTROL <i>CONTROL</i>	On board dimmer/laser On board dimmer/1-10V/laser On/Off
IP <i>IP</i>	20
GUARANTEE <i>GARANTÍA</i>	5 years <i>5 años</i>

FINISH <i>COLOR LUMINARIA</i>	white <i>blanco</i>	black <i>negro</i>
---	------------------------	-----------------------